



ST501

Hinged Glass Lid Chest Freezer

Product Features

- Flat hinged glass lid
- Static cooling
- Castors
- Lock
- Digital temperature display
- Defrost drain

A quality and solidly built commercial display chest freezer from TEFCOLD. The ST range comes with a flat double-glazed glass hinged lid with a robust aluminium frame and lock. A hinged lid is often preferred as customers are less likely to leave the lid open compared to a sliding lid, reducing energy consumption and helping to stop ice forming in the freezer. The cabinet comes with castors fitted as standard. Available in 4 sizes to suit all situations. Ideal for smaller convenience stores, corner shops for storage of ice cream and frozen foods.

| Design and Material | | |
|----------------------------|----------|-----------------------------|
| Tempered glass | | Yes |
| Lid Number & Type | | 1 hinged tempered glass lid |
| Basket Number & Type | | 1 Wire basket, white |
| Max No. of Baskets | pcs | 6 |
| Castors | | 4 double castors |
| Exterior Finish | | White |
| Interior Finish | | White painted steel |
| Lock | | No |
| Measures | | |
| Temperature Range | °C | -24 to -14 |
| Climate Class | | 4 |
| Gross / Net Weight | kg | 88 / 78 |
| Gross / Net Volume | I | 491 / 430 |
| Cooling and Functions | | |
| Type of Controller | | Mechanical |
| Type of Cooling | | Static |
| Type of Defrost | | Manual |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 110 |
| Termometer | | Yes |
| Power and Consumptio | n | |
| Energy Class | | D |
| Energy Consumption | kWh/24h | 2.61 |
| Annual Energy Consumption | kWh/year | 951 |
| Power | | 13 Amp |
| Max Ambient | | 30°C at 55% RH |
| Input Power | W | 191 |
| Voltage / Frequency | V/Hz | 220-240/50 |
| Noise Level | dB(A) | 45 |
| Weight and Dimensions | | |
| Internal Dimension (WxDxH) | mm | 1430 x 510 x 655 |
| External Dimension (WxDxH) | mm | 1550 x 720 x 878 |
| Packed Dimension (WxDxH) | mm | 1640 x 750 x 1000 |
| 40ft Container Load | pcs | 42 |
| | | |





Baskets

Lock